

# Green Pin® Standard Dee Shackles G-4153

with safety bolt

**Material:** Body and pin high tensile steel, Grade 6, quenched and tempered  
**Safety Factor:** MBL equals 6 x WLL  
**Standard:** EN 13889 and meets performance requirements of US Fed Spec RR-C-271, Type IVB Class 3, Grade A  
**Finish:** Hot dipped galvanised  
**Temp Range:** Minus 20°C up to 200°C  
**Certificate:** As above

working load limit	bow dia	pin dia	eye dia	width eye	width inside	length inside	length	length bolt	width nut	product code	weight each
tons	a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm		kg
2	13.5	16	34	13	22	43	81	82	13	12536A	0.39
3.25	16	19	40	16	27	51	97	98	17	12537A	0.67
4.75	19	22	46	19	31	59	112	114	19	12538A	1.08
6.5	22	25	52	22	36	73	134	130	22	12539A	1.66
8.5	25	28	59	25	43	85	154	150	25	12540A	2.46
9.5	28	32	66	28	47	90	167	166	27	12541A	3.40
12	32	35	72	32	51	94	180	178	30	12542A	4.51
13.5	35	38	80	35	57	115	209	197	33	12543A	6.10
17	38	42	88	38	60	127	230	202	19	12544A	7.63
25	45	50	103	45	74	149	271	249	23	12545A	13.25
35	50	57	111	50	83	171	305	269	26	12546A	18.53
42.5	57	65	130	57	95	190	345	301	29	12547A	25.94
55	65	70	145	65	105	203	376	330	32	12548A	35.33
85	75	83	162	73	127	229	427	380	39	12549A	52.97

