

# Collared Eyebolts - Quality Range

## BSW thread

- Material:** BS970-080A27 hardened and tempered  
**Safety Factor:** MBL equals 5 x SWL  
**Standard:** BS4278 - table 4 - 1984  
**Finish:** Self colour  
**Certificate:** This product is supplied with an EC declaration of conformity, upon request a certificate of basic raw material  
**Note:** Electro galvanised (zinc plated) also available - prices on request

safe working load	diameter thread	diameter base	diameter eye outside	diameter eye inside	thickness collar	height	thread length	product code	weight each
tonnes	a inch	b mm	c mm	e mm	f mm	g mm	h mm		kg
0.10	1/4	22	33	15	7	36	18	20101A	0.06
* 0.15	5/16	22	33	15	7	36	18	20102A	0.06
* 0.25	3/8	22	33	15	7	36	18	20103V	0.06
0.50	1/2	29	44	20	10	48	23	20105V	0.15
0.90	5/8	36	52	24	12	58	28	20107V	0.27
1.40	3/4	45	66	30	14	73	35	20108V	0.54
2.00	7/8	52	77	35	17	84	40	20109A	0.85
2.75	1	58	85	39	20	94	46	20110V	1.13
3.50	1.1/8	65	96	44	22	106	51	20111V	1.62
4.50	1.1/4	72	106	48	24	117	56	20112V	2.37
6.50	1.1/2	81	118	54	27	131	63	20114V	3.12
* 9.00	1.3/4	101	148	68	34	164	79	20116A	6.27
12.00	2	115	168	76	38	186	89	20118A	9.58

sizes marked \* are additional and proportional to the specification

