

Collared Eyebolts - Quality Range

UNC thread

Material: BS970-080A27 hardened and tempered
Safety Factor: MBL equals 5 x SWL
Standard: BS4278 - table 4 - 1984
Finish: Self colour
Certificate: This product is supplied with an EC declaration of conformity, upon request a certificate of basic raw material
Note: Electro galvanised (zinc plated) also available - prices on request

safe working load	diameter thread	diameter base	diameter eye outside	diameter eye inside	thickness collar	height	thread length	product code	weight each
tonnes	a inch	b mm	c mm	e mm	f mm	g mm	h mm		kg
* 0.10	1/4	22	33	15	7	36	18	20201	0.06
* 0.15	5/16	22	33	15	7	36	18	20202	0.06
0.25	3/8	22	33	15	7	36	18	20203V	0.06
0.50	1/2	29	44	20	10	48	23	20205V	0.15
0.90	5/8	36	52	24	12	58	28	20207V	0.27
1.40	3/4	45	66	30	14	73	35	20208V	0.54
2.00	7/8	52	77	35	17	84	40	20209V	0.85
2.75	1	58	85	39	20	94	46	20210V	1.13
3.50	1.1/8	65	96	44	22	106	51	20211V	1.62
4.50	1.1/4	72	106	48	24	117	56	20212V	2.37
* 6.50	1.1/2	81	118	54	27	131	63	20214V	3.12
9.00	1.3/4	101	148	68	34	164	79	20216	6.27
12.00	2	115	168	76	38	186	89	20218	9.58

sizes marked * are additional and proportional to the specification

