

Van Beest - Closed Body Rigging Screws

Eye - Eyec/w locknuts

Material: Mild steel
 Safety Factor: MBL equals 5 x WLL, MBL equals 4 x WLL for M45 & M48
 Finish: Hot dipped galvanized
 Certificate: This product is supplied with an EC declaration of conformity
 Note: End fittings of 6 and 8mm rigging screws are electro galvanized



dia thread	length body	length closed position	length open position	dia	length eye inside	width eye inside	working load limit	product code	weight each
a mm	b mm	c mm	d mm	e mm	f mm	g mm	tons		kg
*6	100	165	245	5.5	11	11	0.20	64001B	0.13
*8	108	178	261	6	12	12	0.32	64002B	0.20
*10	125	210	308	8.5	13	13	0.50	64003B	0.60
12	195	325	484	11	30	15	0.70	64004B	0.80
16	230	380	564	12	40	20	1.20	64005B	1.40
20	270	455	673	16	50	24	1.50	64006B	2.40
22	295	495	736	16	50	24	2.20	64007B	3.00
24	325	545	806	19	56	28	3.20	64008B	4.00
33	370	665	961	29	70	35	4.80	64010B	9.00
39	400	725	1032	34	80	40	6.00	64011B	11.50
*45	407	840	1200	30	85	40	8.50	64012B	20.80
*48	407	890	1250	37	92	44	10.00	64013B	24.00

*The above sizes are supplied with Rouna Eyes

