

Van Beest - Closed Body Rigging Screws

Jaw - Jaw c/w locknuts

Material: Mild steel
 Safety Factor: MBL equals 5 x WLL, MBL equals 4 x WLL for M45 & M48
 Finish: Hot dipped galvanized
 Certificate: This product is supplied with an EC declaration of conformity
 Note: End fittings of 6 and 8mm rigging screws are electro galvanized



dia thread	length body	length closed position	length open position	dia pin	length inside	opening jaw	width jaw	dia jaw eye	working load limit	product code	weight each
a mm	b mm	c mm	d mm	e mm	f mm	g mm	h mm	i mm	tons		kg
6	100	175	255	5	19	7	20	13	0.20	64101B	0.16
8	108	199	282	6	25	9	24	14	0.32	64102B	0.27
10	125	222	320	8	26	10.5	28	19	0.50	64103B	0.45
12	195	320	479	10	32	13	34	22	0.70	64104B	0.85
16	230	388	572	12	39	18	42	28	1.20	64105B	1.57
20	270	454	672	16	46	20	51	33	1.50	64106B	2.67
22	295	490	730	20	55	25	55	38	2.20	64107B	3.68
24	325	558	819	22	63	30	70	46	3.20	64108B	5.30
33	370	681	977	30	85	38	82	60	4.80	64110B	12.00
39	400	710	1017	33	86	45	85	76	6.00	64111B	14.20
45	407	810	1170	39	86	48	96	80	8.50	64112B	20.80
48	407	855	1215	45	98	50	101	92	10.00	64113B	24.00

