

Eyebolts with Oval Link

metric coarse thread

Material: BS970-080A27 hardened and tempered
Safety Factor: MBL equals 5 x SWL
Standard: BS4278 - table 2 - 1984
Finish: Self colour
Certificate: This product is supplied with an EC declaration of conformity, upon request a certificate of basic raw material

safe working load	diameter thread	diameter link	length link inside	width link inside	height base to centre	thread length	diameter base	product code	weight each
tonnes	a mm	b mm	c mm	d mm	e mm	f mm	g mm		kg
* 0.10	8	13	53	24	20	27	39	24001	0.33
* 0.15	10	13	53	24	20	27	39	24002	0.35
* 0.20	12	13	53	24	20	27	39	24003	0.36
* 0.30	14	13	53	24	20	27	39	24004	0.37
* 0.40	16	13	53	24	20	27	39	24005	0.38
* 0.70	18	13	53	24	20	27	39	24006	0.39
* 1.00	20	13	53	24	20	27	39	24007	0.40
* 1.30	22	15	63	29	23	32	47	24008	0.65
* 1.60	24	15	63	29	23	32	47	24009	0.66
* 2.50	30	19	80	37	30	41	60	24010	1.31
* 4.00	36	24	102	46	38	52	75	24011	2.69
* 4.50	42	30	126	58	47	65	94	24012	5.31
* 5.00	45	30	126	58	47	65	94	24013	5.35
* 6.30	48	30	126	58	47	65	94	24014	5.50

sizes marked * are additional and proportional to the specification

