


Large Bow Shackles - Quality Range

with type E bolt and nut pin



Material: Body and pin high tensile steel
 Safety Factor: MBL equals 5 x WLL
 Standard: B.S.3032 table 3 - 1958
 Finish: Self colour
 Certificate: As standard an EC declaration of conformity is supplied, upon request a certificate of basic raw material
 Notes: Hot dipped galvanised also available - prices on request

working load limit	diameter bow	diameter pin	diameter eye	inside width	inside length	width bow	product code	weight each
tons	a inch	b inch	c inch	d inch	e inch	f inch		kg
0.15	1/4	3/8	3/4	1/2	1.1/8	3/4	14201	0.09
0.45	3/8	1/2	1	5/8	1.5/8	1	14202	0.21
0.75	1/2	5/8	1.1/4	7/8	2.1/8	1.1/4	4203	0.40
1.25	5/8	3/4	1.1/2	1.1/8	2.3/4	1.5/8	14204	0.70
2.00	3/4	7/8	1.3/4	1.3/8	3.3/8	2	14205	1.25
2.75	7/8	1	2	1.5/8	3.7/8	2.1/4	14206	2.00
3.75	1	1.1/8	2.1/4	1.3/4	4.1/4	2.1/2	14207	2.85
4.75	1.1/8	1.1/4	2.1/2	2	4.7/8	2.7/8	14208	3.94
5.75	1.1/4	1.3/8	2.3/4	2.1/4	5.3/8	3.1/4	420	i:
7.25	1.3/8	1.1/2	3	2.1/2	6	3.1/2		
8.50	1.1/2	1.3/4	3.1/2	2.3/4	6.5/8	3.7/8	14211	9.45
9.50	1.5/8	1.7/8	3.3/4	3	7.3/8	4.3/8	14212	12.67
11.50	1.3/4	2	4	3.3/8	8.1/8	4.3/4	14213	15.85
13.00	1.7/8	2.1/8	4.1/4	3.5/8	8.3/4	5.1/8	14214	18.80
15.00	2	2.1/4	4.1/2	3.7/8	9.3/8	5.1/2	14215	21.56

