

Large Dee Shackles - Quality Range

with type E bolt and nut pin



Material: Body and pin high tensile steel
Safety Factor: MBL equals 5 x WLL
Standard: B.S.3032 table 2 - 1958
Finish: Self colour
Certificate: As standard an EC declaration of conformity is supplied, upon request a certificate of basic raw material
Notes: Hot dipped galvanised also available - prices on request

working load limit	diameter bow	diameter pin	diameter eye	inside width	inside length	product code	weight each
tons	a inch	b inch	c inch	d inch	e inch		kg
0.25	1/4	3/8	3/4	1/2	1	14001	0.10
0.50	3/8	1/2	1	3/4	1.1/2	14002	0.20
0.75	1/2	5/8	1.1/4	1.1/8	2.1/8	14003	0.50
1.50	5/8	3/4	1.1/2	1.1/4	2.1/2	14004	0.68
2.00	3/4	7/8	1.3/4	1.1/2	2.7/8	14005	1.30
3.00	7/8	1	2	1.3/4	3.1/4	14006	1.80
3.75	1	1.1/8	2.1/4	2	3.3/4	14007	2.80
5.00	1.1/8	1.1/4	2.1/2	2.1/8	4.1/8	14008	3.68
6.00	1.1/4	1.3/8	2.3/4	2.3/8	4.1/2	14009	4.92
7.00	1.3/8	1.1/2	3	2.5/8	5	14010	6.00
9.50	1.1/2	1.3/4	3.1/2	2.3/4	5.3/8	14011	9.50
11.25	1.5/8	1.7/8	3.3/4	3	5.3/4	14012	11.56
13.00	1.3/4	2	4	3.1/4	6.1/8	14013	14.92
14.25	1.7/8	2.1/8	4.1/4	3.5/8	7	14014	16.36
16.25	2	2.1/4	4.1/2	3.7/8	7.3/8	14015	19.88
18.00	2.1/8	2.3/8	4.3/4	4.1/8	7.3/4	14016	25.22
20.00	2.1/4	2.1/2	5	4.1/4	8.1/4	14017	29.86

