

# Large Dee Shackle - Quality Range

with type A screw collar pin



**Material:** Body and pin high tensile steel  
**Safety Factor:** MBL equals 5 x WLL  
**Standard:** B.S.3032 table 2 - 1958  
**Finish:** Self colour  
**Certificate:** As standard an EC declaration of conformity is supplied, also upon request a certificate of basic raw material

working load limit	diameter bow	diameter pin	diameter eye	inside width	inside length	product code	weight each
tons	a inch	b inch	c inch	d inch	e inch		kg
0.25	1/4	3/8	3/4	1/2	1	10001A	0.06
0.50	3/8	1/2	1	3/4	1.1/2	10002A	0.16
0.75	1/2	5/8	1.1/4	1.1/8	2.1/8	10003A	0.35
1.50	5/8	3/4	1.1/2	1.1/4	2.1/2	10004A	0.63
2.00	3/4	7/8	1.3/4	1.1/2	2.7/8	10005A	1.00
3.00	7/8	1	2	1.3/4	3.1/4	10006A	1.54
3.75	1	1.1/8	2.1/4	2	3.3/4	10007A	2.21
5.00	1.1/8	1.1/4	2.1/2	2.1/8	4.1/8	10008A	3.11
6.00	1.1/4	1.3/8	2.3/4	2.3/8	4.1/2	10009A	4.33
7.00	1.3/8	1.1/2	3	2.5/8	5	10010A	5.33
9.50	1.1/2	1.3/4	3.1/2	2.3/4	5.3/8	10011A	8.46
11.25	1.5/8	1.7/8	3.3/4	3	5.3/4	10012A	10.48
13.00	1.3/4	2	4	3.1/4	6.1/8	10013A	12.66
14.25	1.7/8	2.1/8	4.1/4	3.5/8	7	10014A	15.34
16.25	2	2.1/4	4.1/2	3.7/8	7.3/8	10015A	18.50
18.00	2.1/8	2.3/8	4.3/4	4.1/8	7.3/4	10016A	23.80
20.00	2.1/4	2.1/2	5	4.1/4	8.1/4	10017A	28.60

